



CHIMICA PORLEZZA s.r.l.
prodotti per l'industria serica

Sede amministrativa e Stabilimento:

Via Antica Regina, 24/b - Loc. LENNO - 22016 TREMEZZINA (Co)

Tel. 0344.55000 - Fax 0344.56347

E-mail: info@chimicaporlezza.com

Codice Univoco: A4707H7

Cap. Soc. € 50.000 i.v.

R.E.A. 1763982

Partita I.V.A. 01982510131



OLIO ANTISTATICO VL4 M2

CONING OIL FOR PES TEXTURIZING PROCESS

• CHARACTERISTICS :

Aspect at 20°C :	clear liquid
Composition:	vegetable fatty-acids esters, non ionic surfactants, antistatic and anti-splash additives
Ionogeneity:	non ionic
Viscosity 20°C	26 - 28 cSt
pH (emulsion 10% water):	6 - 8
Shelf life:	at least 12 months properly stored

• APPLICATION

VL4 M2 is an anti-splash coning oil for texturizing of polyester and for air-jet texturizing of polyester fibers.

• PROPERTIES

- ✓ Excellent antistatic protection
- ✓ Decreases fibre/fibre and fibre/metal friction
- ✓ No oil splashes on the machines, on the floor and in the air
- ✓ Limits dripping on yarn guides
- ✓ High stability to UV light, no yellowing on the yarn
- ✓ Easily and completely removed by scouring process (we suggest our DETERSILK HT)
- ✓ Keeps a constant percentage on the bobbin (outside - inside)
- ✓ Environmentally friendly
- ✓ Complies with the OEKO-TEX standard 100 requirements

• USE PERCENTAGE

- PES for knitting, weaving, no-sized warping 2,5 - 3 %
- PES for sized warping 1 - 2 %
- PES for dyeing 1 %