



CHIMICA PORLEZZA s.r.l.
prodotti per l'industria serica

Sede amministrativa e Stabilimento:

Via Antica Regina, 24/b - Loc. LENNO - 22016 TREMEZZINA (Co)

Tel. 0344.55000 - Fax 0344.56347

E-mail: info@chimicaporlezza.com

Codice Univoco: A4707H7

Cap. Soc. € 50.000 i.v.

R.E.A. 1763982

Partita I.V.A. 01982510131



OLIO ANTISTATICO VL4

OEKO
TEX®

CONING OIL FOR PA,PP and PES TEXTURIZING PROCESS

• CHARACTERISTICS :

Aspect at 20°C :	clear liquid
Composition:	blend of low viscosity white oil highly biodegradable, non ionic surfactants, antistatic and anti-splash additives
Ionogeneity:	non ionic
Viscosity 20°C	18 - 22 cSt
pH (emulsion 10% water):	6 - 8
Shelf life:	at least 12 months properly stored

• APPLICATION

OLIO ANTISTATICO VL4 is an anti-splash coning oil for high speed texturizing, air-jet texturizing and yarn covering of polyamide fibers .

• PROPERTIES

- ✓ Excellent antistatic protection
- ✓ Excellent fibre/fibre and fibre/metal friction coefficient
- ✓ Special for Lycra, doesn't change the tenacity and the elongation of elastomer even after long storage of the covered yarn
- ✓ Gives protection to the knitting needles
- ✓ Does not interfere with the electronic devices on the coning machines
- ✓ Easily and completely removed by scouring process
(we suggest our DETERSILK HT)
- ✓ Certified OEKO-TEX® ECO PASSPORT

• USE PERCENTAGE

- | | |
|-----------------------|-----------|
| ➤ PA texturizing | 1 - 2 % |
| ➤ AIR-JET texturizing | 2 - 2,5 % |
| ➤ YARN covering | 1 - 1,5 |